

SIDEWALK MARKING CODE & CONDITIONS REQUIRING GRIND OR REPLACEMENT



= GRIND

VERTICAL SEPARATION BETWEEN $\frac{1}{2}$ " AND 1". GROUND SURFACE SHALL HAVE A MAXIMUM SLOPE OF 1.5" PER FOOT (1:8). GROUND SURFACES 4" OR MORE IN WIDTH SHALL BE ROUGHENED.



= REMOVE AND REPLACE SIDEWALK, BETWEEN "TEE" MARKS WHEN THE FOLLOWING CONDITIONS APPLY:

- A VERTICAL SEPARATION OF MORE THAN 1" AT EITHER JOINT OR CRACK
- B HORIZONTAL SEPARATION OF 1" OR MORE AT EITHER A JOINT OR A CRACK
- C THE CROSS SLOPE OF SIDEWALK IS GREATER THAN $\frac{3}{4}$ " PER FOOT (1:16)
- D SEVERELY ROUGH, UNEVEN SURFACE DUE TO SPALLING OR SCALING
- E SEVERE CRACKING RESULTING IN MULTIPLE LOOSE OR UNSTABLE INDIVIDUAL PIECES WITHIN A PANEL

				SIDEWALK		
--	--	--	--	----------	--	--

DESIGNED
DRAWN
CHECKED
DATE 11/24/04
SCALE: NTS

CITY OF CORVALLIS
 Public Works Department
 Sidewalk Marking Code

